

## GePro-KNX-panels©



KNX-TAB 15  
anodized  
aluminum



KNX-TAB 16  
anodized black



KNX-TAB 31  
anodized  
aluminum



KNX-TAB 31  
anodized  
aluminum

## GePro surface-mounted housing for KNX panels series 15/16 u. 31/32



Case APAL  
16



case APAL 32

### product features

two-color LED (red / green / OFF)

integrated buzzer

simple installation complete including KNX connection wired ready for connection

extensive software functions

no additional software necessary

no plug-in

Only connect KNX cable, no auxiliary voltage required

Reprogrammable at any time via the KNX with the ETS 5


### technical data



art-no.	KNX-TAB 15	
material	frontplate inscription plate	aluminium aluminium
color	frontplate and inscriptionplate	anodized aluminum nature E6/EV1 - DIN 17611 anodized aluminum black E6/EV6 - DIN 17611
inscription	number of inscription plates labeling area per button	2 (B-Platte 1) ca. 33 x 25 mm
dimensions	inscription plate frontplate AW-case CW-case APAL-case 1x	132 x 50 mm 160 x 260 x 3 mm 142 x 240 x 87 mm 140 x 240 x 72 mm 230 x 310 x 52 mm
operation	number of push button number of keyswitch	15 1
display	LED integrate in buttons	15, red / green
buzzer	number of buzzer	1
connections	KNX-connection (z. B. EIB-Y-St)2x2x0,8) auxiliary voltage	black wire: -KNX red wire: +KNX nothing
weight	without case	ca. 530 g



## technische Daten

art-no.	KNX-TAB 16	
		
material	frontplate inscription plate	aluminium aluminium
color	frontplate and inscriptionplate	anodized aluminum nature E6/EV1 - DIN 17611 anodized aluminum black E6/EV6 - DIN 17611
inscription	number of inscription plates labeling area per button	2 (B-Platte 1)  ca. 33 x 25 mm
dimensions	inscription plate frontplate AW-case CW-case APAL-case 1x	132 x 50 mm 160 x 260 x 3 mm 142 x 240 x 87 mm 140 x 240 x 72 mm 230 x 310 x 52 mm
operation	number of push button number of keyswitch	16 0
display	LED integrate in buttons	16, red / green
buzzer	number of buzzer	1
connections	KNX-connection (z. B. EIB-Y-St)2x2x0,8) auxiliary voltage	black wire: -KNX red wire: +KNX nothing
weight	without case	ca. 530 g



## technical data



art-no.	<b>KNX-TAB 31</b>	
material	frontplate inscription plate	aluminium aluminium
color	frontplate and inscriptionplate	anodized aluminum nature E6/EV1 - DIN 17611 anodized aluminum black E6/EV6 - DIN 17611
inscription	number of inscription plates labeling area per button	4 (B-Platte 1) ca. 33 x 25 mm
dimensions	inscription plate frontplate AW-case APAL-case 1x	132 x 50 mm 299 x 260 x 3 mm 279 x 240 x 87 mm 318 x 280 x 52 mm
operation	number of push button number of keyswitch	31 1
display	LED integrate in buttons	31, red / green
buzzer	number of buzzer	1
connections	KNX-connection (z. B. EIB-Y-St)2x2x0,8) auxiliary voltage	black wire: -KNX red wire: +KNX nothing
weight	without case	ca. 1.050 g

## technical data



art-no.	<b>KNX-TAB 32</b>	
material	frontplate inscription plate	aluminium aluminium
color	frontplate and inscriptionplate	anodized aluminum nature E6/EV1 - DIN 17611 anodized aluminum black E6/EV6 - DIN 17611
inscription	number of inscription plates labeling area per button	4 (B-Platte 1) ca. 33 x 25 mm
dimensions	inscription plate frontplate AW-case APAL-case 1x	132 x 50 mm 299 x 260 x 3 mm 279 x 240 x 87 mm 318 x 280 x 52 mm
operation	number of push button number of keyswitch	32 0
display	LED integrate in buttons	31, red / green
buzzer	number of buzzer	1
connections	KNX-connection (z. B. EIB-Y-St)2x2x0,8) auxiliary voltage	black wire: -KNX red wire: +KNX nothing
weight	without case	ca. 1.030 g




## technical data

art-no.	Gehäuse APAL 16	
number of usable panels	1 panel	
material	aluminium	AlMg3
case depth	2 mm	
dimensions	case	230 x 310 x 52 mm
color	white aluminum RAL 9006 traffic black RAL 9017	structure matt painted  painted satin finish
attachment	case  panel in case	4 wells 4mm at the backside countersunk Allen screw M3
cable entry	1x cable mount	Messing vernickelt IP 68, M16x1,5
gasket	cellular rubber, HY/CR middle 2 mm	nickel plated brass, IP68, M16x1,5 self-stick with H42 mounting aid
weight	incl. gasket and cable mount M16x1,5	ca. 700 g



## technical data

art-no.	Gehäuse APAL 32	
number of usable panels	1 panel	
material	aluminium	AlMg3
case depth	2 mm	
dimensions	case	318 x 280 x 52 mm
color	white aluminum RAL 9006	structure matt painted
attachment	case  panel in case	4 wells 4mm at the backside countersunk Allen screw M3
cable entry	1x cable mount	Messing vernickelt IP 68, M16x1,5
gasket	cellular rubber, HY/CR middle 2 mm	nickel plated brass, IP68, M16x1,5 self-stick with H42 mounting aid
weight	incl. gasket and cable mount M16x1,5	ca. 1250 g



## technical data



### push button

material	Top contact material	stainless steel silver
display	LED	red / green integrated
safety	mechanical	vandal resistant
protection	front switching chamber	IP 40 IP 65
deflection	0,4 mm	
mounting	on the front plate	screwed with O-ring

Reserve technical changes!

The GePro panels are registered as sample registries of the German Patent and Trademark Office.

More information and the product database can be find on our homepage.



GePro – Gesellschaft für Prozesstechnik mbH  
Heinrich-Heine-Ring 78  
18435 Stralsund Germany

Fon: +49 3831 39 00 55  
Fax: +49 3831 39 00 24  
E-Mail: [info@gepro-mv.de](mailto:info@gepro-mv.de)

[www.eib-tab.de](http://www.eib-tab.de)

