


GePro-KNX-buttons®



KNX 4 +
backlight
silver



KNX 4 +
backlight
white



KNX 4 +
backlight
anthrazite



KNX 4 +
backlight
lemon




KNX 4 +
frontlight
black

product features


classic colors & stylish design
 round with RGB LED backlit actuator
 RGB LED colors separately programmable
 round tactile pressure point
 low lift
 front panels backlit
 Commercially available 68er installation box
 functions of a comfort switch programmable with the ETS
 simple installation complete including KNX connection wired ready for connection
 extensive software functions
 no additional software necessary
 no plug-in
 Only connect KNX cable, no auxiliary voltage required
 Reprogrammable at any time via the KNX with the ETS 5

technical data

art-no.	KNX 4 basic element	
dimensions	support ring with mounting holes installation depth of basic element	ca. 70 mm ca. 20 mm
installation	installation in 68er tin	
operation	number of push buttons	4
display	number of LED	4 RGB-LED in push button integrated
connections	KNX-connection (z. B. EIB-Y-St)2x2x0,8) auxiliary voltage	black wire: -KNX red wire: +KNX nothing
weight	without case	ca. 200 g
programming	KNX	up to ETS 4.1 no plug-in no additional software necessary










technical data


art-no.	PAR support ring	
material	sheet steel	stainless ferritic steel
Maße	bore material thickness	ca. 70 mm 0,5 mm
montage	Under basic element KNX 4	on AW or CW Case
weight	without case	ca. 2 g



technical data

art-no.	BL-xx	frontpanel backlight
material	acrylic glas	surface high gloss
dimension	Length x width x depth	75 mm x 75 mm x 6 mm
model	angular, rounded corners	
color	silver	
	red	
	aqua Gray	
	lemon	
	white	
	anthracite	
	silver-white	
type	1-fold 1-fold + socket	further on request
weight	1-fold 1-fold + socket	ca. 25 g ca. 34 g

technical data

art-no.	FL-xx	frontpanel frontlight
material	acrylic glas	surface high gloss
dimension	Length x width x depth	75 mm x 75 mm x 6 mm
model	angular, rounded corners	
color	black	
type	1-fold 1-fold + socket	further on request
weight	1-fold 1-fold + socket	ca. 25 g ca. 34 g



technical data

push button button with LED

material	button	acrylic glass white-opal 24%
Dimension	bore	18 mm
display	RGB-LED	Red / Green / Blue / White Yellow / cyan / Violet
	brightness	adjustable in 7 steps (ETS-parameter)
montage	frontplate	in basic element KNX 4 integrated

Reserve technical changes!

The GePro panels are registered as sample registries of the German Patent and Trademark Office.

More information and the product database can be find on our homepage.



iaft für Prozesstechnik mbH
ng 78
ermany

Fon: +49 3831 39 00 55
Fax: +49 3831 39 00 24
E-Mail: info@gepro-mv.de

www.eib-tab.de

